

EASYCARE

Premium Décor Interior/Exterior Waterbased Acrylic Enamel

DESCRIPTION

A premium quality interior/exterior acrylic paint. This low odor, environmentally friendly product is extra durable and washable.

- **PDL FORMULA ANALYSIS-WHITE**
- Resin Type-Acrylic Latex
- Sheen/Type Finish:
- 65 + at 60°/Gloss
- Weight per Gallon = 10.2
- Percent Solids by Weight = 46.3
- Percent Solids by Volume = 34.8
- Viscosity = 90-100 KU
- V.O.C. = Less than 50g/L.



PRODUCT FEATURES

- Fast Drying
- Soap & Water Clean-up
- One Coat Coverage

COLORS & BASES

- | | |
|---------------------|----------------------------------|
| PDL-1 Gloss White | PDL-40 Sunflower Yellow |
| PDL-2 Gloss Black | PDL-50 Hunter Green |
| PDL-3 Satin White | PDL-60 Leather Brown |
| PDL-12 Ivory | PDL-70 Slate Gray |
| PDL-16 Almond | PDL-71 Pewter Gray |
| PDL-30 Royal Blue | PDL-96 Fiesta Red |
| PDL-33 Country Blue | PDL-97 Hot Red |
| | Pastel, Tint, Deep, Neutral Base |

RECOMMENDED USE

Indoor or outdoor furniture, primed wood or primed metal, wood trim and crafts. Not recommended for use as a house paint.

THINNING: DO NOT THIN.

DRY TIME: Dries in 2 - 4 hours. Repeat if necessary after 8 hours. May be cleaned gently with non-abrasive cleaner after 3 days. Low temperature or high humidity may increase dry time.

COVERAGE: 400 sq. ft. per gallon

CLEAN UP: Wash tools with soap and water immediately after painting. Remove paint spatters promptly with a wet cloth. Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

APPLICATION METHOD

Stir or mix paint before using and intermix all containers for color uniformity. As-is 1 - 2 coats with brush or paint pad. Thin sparingly with water if necessary for spraying. Do not overspread. Average coverage 400 sq. ft. per gallon.

SURFACE PREP

- Remove dirt, mildew, grease, wax & soap residue.
- Dull glossy areas with sandpaper.
- Sand rough surfaces smooth.
- Prime bare wood with proper oil base primer.
- On metal, use proper metal primer.