

EASYCARE

Exterior Natural Deck, Siding & Fence Stain - WNC

DESCRIPTION

100% Acrylic Natural Deck, Siding & Fence Stain for natural or pressure treated wood decks, siding & fences. Helps wood stand up to the harshest weather elements.

WNC FORMULA ANALYSIS

Resin Type – Acrylic Latex

Sheen/Type Finish:

0-20 @60° / Penetrating Stain

Weight per Gallon = 14.37 lbs.

Percent Solids by Weight = 14.37

Percent Solids by volume = 12.53

Viscosity Range = 60-70 KU

V.O.C. = Less than 100 g/L



PRODUCT FEATURES

- Ideal for natural or pressure-treated wood decks, siding & fences
- Transparent coating enhances natural wood grain & color
- Ultraviolet reflectors retard graying & sun damage
- Water repellent coating resists scuffing

RECOMMENDED USE

Exterior above ground natural & pressure-treated woods including cedar, redwood, fir and pine. Also provides excellent protection while maintaining natural appearance to siding, shakes, wood shingles, landscape timbers and decks. MPI approved.

THINNING: DO NOT THIN

DRY TIME: 77°F @50% humidity: Dry to the touch within 2 to 4 hours. Recoat usually within 24 hours. High humidity or low temperatures may increase dry time.

COVERAGE: 150-350 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat, depending on the porosity of the wood.

CLEAN UP & DISPOSAL: Wash tools with warm water and soap immediately after application.

Call 1-800-CLEANUP (USA only) or visit www.Earth911.org. Properly dispose of used rags. Protect unused portion from freezing

STORAGE: Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

APPLICATION METHOD

- Apply only to bare wood surfaces that have been properly prepared and cleaned..
- ONLY ONE COAT IS RECOMMENDED
- Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 50°F
- Do not apply in hot sun.
- Stir thoroughly before and during use.
- Intermix all containers for uniform color.
- Use a premium brush or pad applicator.
- A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood.
- DO NOT OVER APPLY.
- Spread well, do not puddle or accumulate on wood surface.
- Moving left to right, apply to two or three boards at a time leaving a “wet edge” to prevent lapping.
- Saturate end grain.