

EASYCARE™

Exterior Solid Color Siding & Fence Stain - WSOV

DESCRIPTION

Oil Base Solid Color Siding & Fence Stain for natural or pressure treated wood siding & fences.

WSOV FORMULA ANALYSIS:

Resin Type-Acrylic modified alkyd emulsion

Sheen/Type Finish:

0-15 @60° / Penetrating Stain

Weight per Gallon = 9.20 lbs.

Percent Solids by Weight = 28.80

Percent Solids by volume = 21.50

Viscosity Range = 77-83 KU

V.O.C. = Less than 250 g/L

RECOMMENDED USE

Exterior above ground natural & pressure-treated structures such as wood siding, fences, shingles, shakes, clapboard, rough sawn siding and plywood. Not recommended for decks.

DRY TIME, THINNING & TINTING: Allow 12-15 hours between coats. Dries thoroughly usually within 24 hours. High humidity or low temperatures may increase dry time. (DO NOT THIN). Fully tintable.

COVERAGE: 150-350 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon depending on the porosity of the wood.

CLEAN UP & DISPOSAL: Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags. Protect unused portion from freezing. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or visit www.Earth911.org.

APPLICATION METHOD

- DO NOT APPLY TO DECKS
- Apply only to properly prepared and cleaned wood surfaces.
- On non-porous surfaces apply only one coat, as two coats may result in a high sheen finish.
- On very porous or severely weathered wood two coats may necessary.
- Do not apply if rain or dew is expected within 48 hrs or if outside temperature could drop below 40° F
- Do not apply in hot sun.
- Stir thoroughly before and during use.
- Intermix all containers for uniform color.
- Use a premium brush or pad applicator.
- A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood.
- DO NOT OVER APPLY.
- Spread well, do not puddle or accumulate on wood surface.
- Moving left to right, apply to two or three boards at a time leaving a “wet edge” to prevent lapping.
- Saturate end grain.



PRODUCT FEATURES

- Ideal for natural or pressure-treated wood siding, trim & fences
- High viscosity formula for easy application
- Tough, water repellent coating
- Mildew & peel resistant coating