

# Safety Data Sheet

## 1. Identification

**Product Information:** PDS-6

**Product Name:** Premium Decor Decorative Enamels (360 Spray Tip) - FLAT BLACK

**Recommended Use:** Aerosol Paint

**Application Method:** Refer to Product Label

**Supplied by:** GPM  
201 Jandus Road  
Cary, IL 60013  
Telephone: (847) 639-5383

**Emergency Telephone:** (866)257-3981

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** Extremely Flammable!

### GHS Classification

Carc. 1B, Comp. Gas, Eye Irrit. 2, Fl Aer, 1, Muta. 1B, Repr. 2, STOT SE 3 NE

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

61% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

|  |      |   |
|--|------|---|
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.   |
| Carcinogenicity, category 1B           | H350 | Suspected of causing cancer.  |
| Compressed Gas                         | H280 | Contains gas under pressure; may explode if heated.   |
| Eye Irritation, category 2             | H319 | Causes serious eye irritation.  |
| Flammable Aerosol, category 1          | H222 | Extremely flammable aerosol.  |
| Germ Cell Mutagenicity, category 1B    | H340 | Suspected of causing genetic defects .  |
| Reproductive Toxicity, category 2      | H361 | Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies. |
| STOT, single exposure, category 3, NE  | H336 | May cause drowsiness or dizziness.  |

### GHS LABEL PRECAUTIONARY STATEMENTS

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source.  |
| P251 | Do not pierce or burn, even after use.   |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                     |
| P281 | Use personal protective equipment as required.   |

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313

IF exposed or concerned: Get medical advice/attention.

P312

Call a POISON CENTER or doctor/physician if you feel unwell.

P337+P313

If eye irritation persists: Get medical advice/attention.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

P410+P403

Protect from sunlight. Store in a well-ventilated place.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

### 3. Composition/Information on Ingredients

| Chemical Name                                | CAS-No.    | Wt. %   | GHS Symbols       | GHS Statements           |
|--|------------|---------|-------------------|--------------------------|
| ACETONE                                      | 67-64-1    | 25-50   | GHS02-GHS07       | H225-319-332-336         |
| PROPANE                                      | 74-98-6    | 10-25   | GHS04             | H280                     |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8 | 10-25   | GHS08             | H304-340-350             |
| BUTANE                                       | 106-97-8   | 2.5-10  | GHS04-GHS08       | H280-340                 |
| TALC   | 14807-96-6 | 2.5-10  | No Information    | No Information           |
| TOLUENE                                      | 108-88-3   | 2.5-10  | GHS02-GHS07-GHS08 | H225-304-315-336-361-373 |
| CARBON BLACK                                 | 1333-86-4  | 1.0-2.5 | No Information    | No Information           |
| XYLENE                                       | 1330-20-7  | 1.0-2.5 | GHS02-GHS07       | H226-312-315-332         |
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT  | 64742-47-8 | 0.1-1.0 | GHS08             | H304-340-350             |
| ETHYLBENZENE                                 | 100-41-4   | 0.1-1.0 | GHS02-GHS07-GHS08 | H225-304-315-319-332-373 |
| SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC  | 64742-94-5 | 0.1-1.0 | GHS06-GHS08       | H304-330                 |
| STODDARD SOLVENT NAPHTHA                     | 8052-41-3  | 0.1-1.0 | GHS08             | H304-340-350-372         |
|  | 8030-30-6  | 0.1-1.0 | GHS08             | H304-340-350             |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



**FIRST AID - INHALATION:** Remove to fresh air. Give oxygen or artificial respiration if necessary. DO NOT use mouth to mouth resuscitation. Seek medical attention.

**FIRST AID - SKIN CONTACT:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. Get medical attention if irritation develops or persists.

**FIRST AID - EYE CONTACT:** Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.

**FIRST AID - INGESTION:** If ingested, do not induce vomiting. Immediately give two glasses of water or activated charcoal slurry. Never give anything by mouth to an unconscious person. Call a physician.

### 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full face mask in a positive pressure demand mode. Treat as a volatile liquid fire. Water spray may be ineffective. If water spray is used, fog nozzles are preferable. Water may be used to cool sealed containers to prevent pressure build-up and possible explosion or auto-ignition when exposed to the heat of a fire.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

### 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** REMOVE ALL SOURCES OF IGNITION FROM THE

SPILL AREA. EVACUATE ALL NON-ESSENTIAL PERSONNEL UPWIND. USING NON-SPARKING TOOLS, SOAK UP SPILLED MATERIAL / SWEEP UP MATERIAL WITH ABSORBENTS AND PLACE IN A CONTAINER FOR DISPOSAL.

## 7. Handling and Storage



**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

**STORAGE:** Keep container closed when not in use. Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u>                                     | <u>ACGIH TLV-TWA</u>                         | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u>                          | <u>OSHA PEL-CEILING</u> |
|--|--|-----------------------|--|-------------------------|
| ACETONE  | 500 PPM                                      | 500 PPM               | 1000 PPM, 2400 mg/m <sup>3</sup>             | N.E.                    |
| PROPANE  | N.E.   | N.E.                  | 1000 PPM, 1800 mg/m <sup>3</sup>             | N.E.                    |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC             | N.E.   | N.E.                  | 500 PPM, 2000 mg/N.E. m <sup>3</sup>         |                         |
| BUTANE   | N.E.   | 1000 PPM              | N.E.   | N.E.                    |
| TALC   | 2 mg/m <sup>3</sup><br>(Respirable fraction) | N.E.                  | 2 mg/m <sup>3</sup><br>(Respirable fraction) | N.E.                    |
| TOLUENE  | 20 PPM                                       | N.E.                  | 200 PPM                                      | 300 PPM                 |
| CARBON BLACK   | 3 mg/m <sup>3</sup>                          | 7 mg/m <sup>3</sup>   | 3.5 mg/m <sup>3</sup>                        | N.E.                    |
| XYLENE   | 100 PPM                                      | 150 PPM               | 100 PPM                                      | N.E.                    |
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT ETHYLBENZENE | 100 ppm                                      | N.E.                  | N.E.   | N.E.                    |
|  | 20 PPM                                       | 125 PPM               | 100 PPM, 435 mg/m <sup>3</sup>               | N.E.                    |
| SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC              | N.E.   | N.E.                  | N.E.   | N.E.                    |
| STODDARD SOLVENT   | 100 PPM, 2900 mg/m <sup>3</sup>              | N.E.                  | 500 PPM, 525 mg/m <sup>3</sup>               | N.E.                    |
| NAPHTHA  | 400 mg/m <sup>3</sup>                        | N.E.                  | 400 mg/m <sup>3</sup>                        | N.E.                    |

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



**SKIN PROTECTION:** Chemical-resistant gloves may be required for individuals with sensitive skin.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



**OTHER PROTECTIVE EQUIPMENT:** Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

## 9. Physical and Chemical Properties

|                                      |                           |  |                |
|--------------------------------------|---------------------------|--|----------------|
| <b>Appearance:</b>                   | Black Aerosol Mist        | <b>Physical State:</b>                         | Liquid         |
| <b>Odor:</b>                         | Solvent Odor              | <b>Odor Threshold:</b>                         | No Information |
| <b>Density, g/cm<sup>3</sup>:</b>    | 0.000                     | <b>pH:</b>                                     | No Information |
| <b>Freeze Point, °C:</b>             | No Information            | <b>Viscosity:</b>                              | No Information |
| <b>Solubility in Water:</b>          | No Information            | <b>Partition Coefficient, n-octanol/water:</b> | No Information |
| <b>Decomposition temperature, °C</b> | No Information            |  |                |
| <b>Boiling Range, °C:</b>            | -29                       | <b>Explosive Limits, %:</b>                    | N/A            |
| <b>Combustibility:</b>               | Supports Combustion       | <b>Flash Point, °C:</b>                        | -95            |
| <b>Evaporation Rate:</b>             | Faster than Diethyl Ether | <b>Auto-Ignition Temperature, °C</b>           | No Information |
| <b>Vapor Density:</b>                | Heavier than Air          | <b>Vapor Pressure, mmHg:</b>                   | No Information |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Do not expose to temperatures above 120 °F (49 °C). Avoid heat, flames, sparks and other sources of ignition. Avoid contact with strong acids, strong bases and strong oxidizing agents.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames. Strong acids and strong bases

**HAZARDOUS DECOMPOSITION PRODUCTS:** Incomplete combustion may produce carbon monoxide and other toxic gases.

## 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Exposure to large amounts of vapors or spray mists may cause irritation to the lungs, nose, and throat. May also cause dizziness, nausea, fatigue, or headache. Prolonged overexposure may cause coughing, shortness of breath, dizziness, and intoxication.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Mist and vapors may cause eye irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

**CARCINOGENICITY:** IARC lists Ethylbenzene and Carbon Black as possible human carcinogens (group 2B)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u>                         | <u>Oral LD50</u>        | <u>Dermal LD50</u>      | <u>Vapor LC50</u>  |
|----------------|--|-------------------------|-------------------------|--------------------|
| 67-64-1        | ACETONE                                      | 5800 mg/kg              | 20000 mg/kg             | N.I.               |
| 64742-89-8     | SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | >2000 mg/kg (Rat)       | >3000 mg/kg (Rabbit)    | >5000 PPM/1h (Rat) |
| 14807-96-6     | TALC   | >5000 mg/m <sup>3</sup> | >2000 mg/m <sup>3</sup> | N.I.               |
| 108-88-3       | TOLUENE                                      | >7,000 mg/kg            | >12,000 mg/kg           | >30.0 mg/l         |

|            |  |                  |                      |                     |
|------------|--|------------------|----------------------|---------------------|
| 1333-86-4  | CARBON BLACK                                   | >8000 mg/kg      | >3000 mg/kg          | N.I.                |
| 1330-20-7  | XYLENE   | 3523 mg/kg       | 1700 mg/kg           | N.I.                |
| 64742-47-8 | DISTILLATES (PETROLEUM),<br>HYDROTREATED LIGHT | >5000 mg/kg      | >5000 mg/kg          | N.I.                |
| 100-41-4   | ETHYLBENZENE                                   | 3500 mg/kg       | 17000 mg/kg          | 17.2 mg/l (Rat)     |
| 64742-94-5 | SOLVENT NAPHTHA (PETROLEUM),<br>HEAVY AROMATIC | 3000 mg/kg (Rat) | >3000 mg/kg (Rabbit) | >0.2 mg/l/4hr (Rat) |
| 8052-41-3  | STODDARD SOLVENT                               | >5000 mg/kg      | >3000 mg/kg          | N.I.                |

N.I. = No Information

## 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

## 13. Disposal Information



Product

**DISPOSAL METHOD:** Dispose of material in accordance with applicable federal, state and local regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** REMOVE ALL SOURCES OF IGNITION FROM THE SPILL AREA. EVACUATE ALL NON-ESSENTIAL PERSONNEL UPWIND. USING NON-SPARKING TOOLS, SOAK UP SPILLED MATERIAL / SWEEP UP MATERIAL WITH ABSORBENTS AND PLACE IN A CONTAINER FOR DISPOSAL.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** Note: This product can be transported as a LIMITED QUANTITY

|                                  |                |                          |                |
|----------------------------------|----------------|--------------------------|----------------|
| <b>DOT Proper Shipping Name:</b> | Aerosols       | <b>Packing Group:</b>    | No Information |
| <b>DOT Technical Name:</b>       | No Information | <b>Hazard SubClass:</b>  | No Information |
| <b>DOT Hazard Class:</b>         | 2.1            | <b>Resp. Guide Page:</b> | No Information |
| <b>DOT UN/NA Number:</b>         | 1950           |                          |                |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| RESIN                | Proprietary    |

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| CARBON BLACK         | 1333-86-4      |
| ETHYLBENZENE         | 100-41-4       |
| NAPHTHALENE          | 91-20-3        |
| CRYSTALLINE SILICA   | 14808-60-7     |

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| TOLUENE              | 108-88-3       |

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class** No Information

**16. Other Information**

|                               |                       |                         |          |
|-------------------------------|-----------------------|-------------------------|----------|
| <b>Revision Date:</b>         | 2/1/2017              | <b>Supersedes Date:</b> | New MSDS |
| <b>Reason for revision:</b>   | No Information        |                         |          |
| <b>Datasheet produced by:</b> | Regulatory Department |                         |          |

**HMIS Ratings:**

|                |    |                      |   |                    |   |                             |      |
|----------------|----|----------------------|---|--------------------|---|-----------------------------|------|
| <b>Health:</b> | *2 | <b>Flammability:</b> | 4 | <b>Reactivity:</b> | 0 | <b>Personal Protection:</b> | N.I. |
|----------------|----|----------------------|---|--------------------|---|-----------------------------|------|

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

|      |   |
|------|---|
| H225 | Highly flammable liquid and vapour.   |
| H226 | Flammable liquid and vapor.   |
| H280 | Contains gas under pressure; may explode if heated.   |
| H304 | May be fatal if swallowed and enters airways.   |
| H312 | Harmful in contact with skin.   |
| H315 | Causes skin irritation.   |
| H319 | Causes serious eye irritation.  |
| H330 | Fatal if inhaled.   |
| H332 | Harmful if inhaled.   |
| H336 | May cause drowsiness or dizziness.  |
| H340 | Suspected of causing genetic defects.   |
| H350 | Suspected of causing cancer.  |
| H361 | Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies. |
| H372 | Causes damage to organs   |
| H373 | May cause damage to organs through prolonged or repeated exposure.  |

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS04



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.