

Safety Data Sheet

1. Identification

Product Information: ECS1

Product Name: EasyCare 365 Interior Semi-Gloss Latex Paint & Primer - WHITE

Recommended Use: Interior Non-Flat Latex Paint

Application Method: Refer to Product Label

Supplied by: True Value Manufacturing
201 Jandus Road
Cary, IL 60013
Telephone: (847) 639-5383

Emergency Telephone: (866)257-3981

2. Hazards Identification

EMERGENCY OVERVIEW: This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

GHS Classification

No GHS Classifications were found

Symbol(s) of Product

No GHS Symbols Exist

Signal Word

No Signal Word has been assigned

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
TITANIUM DIOXIDE	13463-67-7	10-25	No Information	No Information
ALUMINIUM HYDROXIDE	21645-51-2	0.1-1.0	GHS07	H332
AMMONIUM HYDROXIDE	1336-21-6	0.1-1.0	GHS05-GHS07	H302-314-332-335
AMMONIA	7664-41-7	0.1-1.0	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

FIRST AID - EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

FIRST AID - INGESTION: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

7. Handling and Storage



HANDLING: KEEP FROM FREEZING.

STORAGE: Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
TITANIUM DIOXIDE	10 mg/m ³	N.E.	15 mg/m ³ (Total dust)	N.E.
ALUMINIUM HYDROXIDE	3 mg/m ³ (Respirable particles)	N.E.	5 mg/m ³ (Respirable fraction)	N.E.
AMMONIUM HYDROXIDE	25 ppm	35 ppm	50 ppm	N.E.
AMMONIA	25 ppm	35 ppm	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



SKIN PROTECTION: Sensitive individuals should wear gloves to prevent repeated contact.



EYE PROTECTION: Safety glasses with side-shields



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: Wash hands before eating, drinking, or smoking.

9. Physical and Chemical Properties

Appearance:	Thick White Liquid	Physical State:	Liquid
Odor:	Slight Ammonia Odor	Odor Threshold:	No Information
Density, g/cm³:	1.230	pH:	No Information
Freeze Point, °C:	No Information	Viscosity:	No Information
Solubility in Water:	No Information	Partition Coefficient, n-octanol/water:	No Information
Decomposition temperature, °C	No Information		
Boiling Range, °C:	98 - 104	Explosive Limits, %:	N/A
Combustibility:	Does not Support Combustion	Flash Point, °C:	Not Applicable
Evaporation Rate:	Slower than Ether	Auto-Ignition Temperature, °C	No Information
Vapor Density:	Lighter than Air	Vapor Pressure, mmHg:	No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND FREEZING.

INCOMPATIBILITY: No Information

HAZARDOUS DECOMPOSITION PRODUCTS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

EFFECT OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.

EFFECT OF OVEREXPOSURE - INGESTION: May be harmful if swallowed. May cause gastrointestinal disturbance.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

CARCINOGENICITY: IARC lists Titanium Dioxide as a possible human carcinogen (Group 2B)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	TITANIUM DIOXIDE	> 5,000 mg/kg (Rat)	> 10,000 mg/kg (Rabbit)	N.I.
21645-51-2	ALUMINIUM HYDROXIDE	> 2,000 mg/kg (Rat)	N.I.	N.I.
1336-21-6	AMMONIUM HYDROXIDE	350 mg/kg (Rat)	> 2,000 mg/kg (Rat)	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No Information

13. Disposal Information



Product

DISPOSAL METHOD: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Name:	No Information	Packing Group:	No Information
DOT Technical Name:	No Information	Hazard SubClass:	No Information
DOT Hazard Class:	No Information	Resp. Guide Page:	No Information
		DOT UN/NA Number:	No Information

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
AMMONIUM HYDROXIDE	1336-21-6
IODOPROPYNYL BUTYLCARBAMATE	55406-53-6
2,2-DIBROMO-2-CYANOACETAMIDE	10222-01-2

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name

WATER
VINYL ACRYLIC POLYMER
STYRENE/ACRYLIC COPOLYMER

CAS-No.

7732-18-5
Proprietary
Proprietary

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name

WATER
VINYL ACRYLIC POLYMER

CAS-No.

7732-18-5
Proprietary

CALIFORNIA PROPOSITION 65 CARCINOGENS**WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name

CRYSTALLINE SILICA
ACRYLONITRILE
ETHYL ACRYLATE
ETHYLENE OXIDE
BENZYL CHLORIDE
1,4-DIOXANE

CAS-No.

14808-60-7
107-13-1
140-88-5
75-21-8
100-44-7
123-91-1

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name

ETHYLENE OXIDE

CAS-No.

75-21-8

International Regulations: As follows -**CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class No Information

16. Other Information

Revision Date: 2/20/2018 **Supersedes Date:** New MSDS

Reason for revision: No Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	N.I.
----------------	---	----------------------	---	--------------------	---	-----------------------------	------

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS05



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.