# **Safety Data Sheet**

## 1. Identification

Product Information: ECSET

Product Name: EasyCare 365 Interior Satin Latex Wall Paint & Primer - TINT BASE

Recommended Use: Interior Non-Flat Latex Paint

Application Method: Refer To Product Label

Supplied by: True Value Manufacturing

201 Jandus Road Cary, IL 60013

Telephone: (847) 639-5383

Emergency Telephone: (866)257-3981

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### **GHS Classification**

No GHS Classifications were found

#### Symbol(s) of Product

No GHS Symbols Exist

#### Signal Word

No Signal Word has been assigned

#### Possible Hazards

14% of the mixture consists of ingredients of unknown acute toxicity

# 3. Composition/Information on Ingredients

Chemical NameCAS-No.Wt. %GHS SymbolsGHS StatementsTITANIUM DIOXIDE13463-67-710-25No InformationNo InformationLIMESTONE1317-65-31.0-2.5No InformationNo Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



FIRST AID - INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

FIRST AID - EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

**FIRST AID - INGESTION:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

# 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressuredemand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

# 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

# 7. Handling and Storage





HANDLING: KEEP FROM FREEZING.

STORAGE: Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> <u>OSHA PEL-CEILING</u>

TITANIUM DIOXIDE 10 mg/m3 N.E. 15 mg/m3 (Total N.E. dust)

LIMESTONE 5 mg/m3 N.E. 5 mg/m3 N.E. 5 mg/m3 N.E. (Respirable fraction) (Respirable fraction)

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### Personal Protection



**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



SKIN PROTECTION: Sensitive individuals should wear gloves to prevent repeated contact.



EYE PROTECTION: Safety glasses with side-shields



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** Wash hands before eating, drinking, or smoking.

# 9. Physical and Chemical Properties

Appearance: Thick White Liquid Physical State: Liquid

Odor: **Odor Threshold:** No Information Slight Ammonia Odor Density, lb/gal: pH: 9.51 - 9.919.0 - 9.5Freeze Point, °C: No Information Viscosity: No Information Partition Coefficient, n-octanol/ Solubility in Water: No Information No Information

Decomposition temperature, °C No Information water:

Boiling Range, °C: 98 - 104 Explosive Limits, %: N/A

Combustibility:Does Not Support Combustion<br/>Slower Than EtherFlash Point, °C:Not ApplicableEvaporation Rate:Slower Than EtherAuto-Ignition Temperature, °CNo InformationVapor Density:Lighter Than AirVapor Pressure, mmHg:No Information

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND FREEZING.

**INCOMPATIBILITY:** No Information

HAZARDOUS DECOMPOSITION PRODUCTS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. MAY

GENERATE CARBON MONOXIDE GAS.

# 11. Toxicological Information



#### **Practical Experiences**

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

**EFFECT OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.** 

EFFECT OF OVEREXPOSURE - INGESTION: May be harmful if swallowed. May cause gastrointestinal disturbance.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

CARCINOGENICITY: IARC lists Titanium Dioxide as a possible human carcinogen (Group 2B)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
13463-67-7	TITANIUM DIOXIDE	> 5,000 mg/kg (Rat)	> 10,000 mg/kg	N.I.
			(Rabbit)	
1317-65-3	LIMESTONE	6,450 mg/kg (Rat)	> 2,000 mg/kg	N.I.
			(Rabbit)	

N.I. = No Information

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

# 13. Disposal Information



#### **Product**

**DISPOSAL METHOD:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

# 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: Not Regulated

DOT Proper Shipping Name: NA Packing Group: NA

Hazard SubClass: NA

DOT Technical Name: NA Resp. Guide Page: No Information

DOT Hazard Class: NA DOT UN/NA Number: No Information

# 15. Regulatory Information

# U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

## **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.AMMONIUM HYDROXIDE1336-21-6

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

# U.S. State Regulations:

## **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.WATER7732-18-5VINYL ACRYLIC POLYMERProprietarySTYRENE/ACRYLIC COPOLYMERProprietary

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.WATER7732-18-5VINYL ACRYLIC POLYMERProprietary

## **CALIFORNIA PROPOSITION 65 CARCINOGENS**



Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

 Chemical Name
 CAS-No.

 CRYSTALLINE SILICA
 14808-60-7

 ACRYLONITRILE
 107-13-1

 ETHYL ACRYLATE
 140-88-5

 ETHYLENE OXIDE
 75-21-8

 1,4-DIOXANE
 123-91-1

 BENZYL CHLORIDE
 100-44-7

## **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**



Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical NameCAS-No.ETHYLENE OXIDE75-21-8

## International Regulations: As follows -

## **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class No Information

## 16. Other Information

Revision Date: 7/26/2018 Supersedes Date: New MSDS

Reason for revision: No Information

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: N.I.

## Icons for GHS Pictograms shown in Section 3 describing each ingredient:

No GHS Pictograms exist for Section 3

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.