

# Safety Data Sheet

## 1. Identification

**Product Information:** MP502-B  
**Product Name:** Mythic Black Label Interior Semi-Gloss - MEDIUM BASE  
**Recommended Use:** Interior Non-Flat Latex Paint  
**Application Method:** Refer To Product Label  
**Supplied by:** GPM  
 201 Jandus Road  
 Cary, IL 60013  
 Telephone: (847) 639-5383  
**Emergency Telephone:** (866)257-3981

## 2. Hazards Identification

**HAZARDS OVERVIEW:** This product **IS NOT CONSIDERED HAZARDOUS** by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### GHS Classification

No GHS Classifications were found

### Symbol(s) of Product

No GHS Symbols Exist

### Signal Word

No Signal Word has been assigned

### Possible Hazards

12% of the mixture consists of ingredients of unknown acute toxicity

## 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
TITANIUM DIOXIDE	13463-67-7	10-25	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



**FIRST AID - INHALATION:** Remove person to fresh air. If signs/symptoms continue, get medical attention.

**FIRST AID - SKIN CONTACT:** WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

**FIRST AID - EYE CONTACT:** FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

**FIRST AID - INGESTION:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

## 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Container may rupture on heating.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** No Information

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

## 7. Handling and Storage



**HANDLING:** KEEP FROM FREEZING.

**STORAGE:** Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
TITANIUM DIOXIDE	10 mg/m3	N.E.	15 mg/m3 (Total dust)	N.E.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



**SKIN PROTECTION:** Sensitive individuals should wear gloves to prevent repeated contact.



**EYE PROTECTION:** Safety glasses with side-shields



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** Wash hands before eating, drinking, or smoking.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Thick Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Slight Ammonia Odor	<b>Odor Threshold:</b>	No Information
<b>Density, lb/gal:</b>	9.29 - 9.69	<b>pH:</b>	No Information
<b>Freeze Point, °C:</b>	No Information	<b>Viscosity:</b>	No Information
<b>Solubility in Water:</b>	No Information	<b>Partition Coefficient, n-octanol/ water:</b>	No Information
<b>Decomposition temperature, °C</b>	No Information		
<b>Boiling Range, °C:</b>	98 - 104	<b>Explosive Limits, %:</b>	N/A
<b>Combustibility:</b>	Does Not Support Combustion	<b>Flash Point, °C:</b>	Not Applicable
<b>Evaporation Rate:</b>	Slower Than Ether	<b>Auto-Ignition Temperature, °C</b>	No Information
<b>Vapor Density:</b>	Lighter Than Air	<b>Vapor Pressure, mmHg:</b>	No Information

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**STABILITY:** THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

**CONDITIONS TO AVOID:** AVOID HIGH TEMPERATURES AND FREEZING.

**INCOMPATIBILITY:** No Information

**HAZARDOUS DECOMPOSITION PRODUCTS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

## 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** MILD EYE IRRITANT.

**EFFECT OF OVEREXPOSURE - INGESTION:** May be harmful if swallowed. May cause gastrointestinal disturbance.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

**CARCINOGENICITY:** IARC lists Titanium Dioxide as a possible human carcinogen (Group 2B) by route of inhalation.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	TITANIUM DIOXIDE	> 5,000 mg/kg (Rat)	> 10,000 mg/kg (Rabbit)	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

## 13. Disposal Information



Product

**DISPOSAL METHOD:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** Not Regulated by DOT

<b>DOT Proper Shipping Name:</b>	Not Regulated	<b>Packing Group:</b>	Not Regulated
<b>DOT Technical Name:</b>	Not Regulated	<b>Hazard SubClass:</b>	Not Regulated
<b>DOT Hazard Class:</b>	Not Regulated	<b>Resp. Guide Page:</b>	No Information
		<b>DOT UN/NA Number:</b>	Not Regulated

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
WATER	7732-18-5
ACRYLIC POLYMER	Proprietary
Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	94-28-0

