

# Safety Data Sheet

## 1. Identification

**Product Information:** VE-4

**Product Name:** EasyCare Basics Oil Gloss Floor & Utility Enamel - TILE RED

**Recommended Use:** Non-Flat Solvent Based Paint

**Application Method:** Refer to Product Label

**Supplied by:** GPM  
201 Jandus Road  
Cary, IL 60013  
Telephone: (847) 639-5383

**Emergency Telephone:** (866)257-3981

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** FLAMMABLE liquid and vapor. This product does contain a material which can cause cancer. Crystalline silica has been classified by IARC and NTP as a carcinogen for humans (Group 1) from lab animal studies. Risk of cancer depends on duration and level of exposure from sanding surfaces or spray mist. When sanding or spraying product use (NIOSH/MSHA approved) respiratory protection.

### GHS Classification

Carc. 1A, Flam. Liq. 3, STOT RE 2

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

8% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependant on ingredient form.
Flammable Liquid, category 3	H226	Flammable liquid and vapor.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

### GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.

### GHS ADDITIONAL INFORMATION

H362 Contains one or more Category 1 or Category 2 Reproductive Toxicants at greater than 0.1%. A Safety Data Sheet shall be available for the mixture upon request.

### GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting/.../ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.

## 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT LIMESTONE	64742-47-8	10-25	GHS08	H304
IRON OXIDE (FE2O3), RESPIRABLE	1317-65-3	10-25	No Information	No Information
POLYURETHANE RESIN	1309-37-1	2.5-10	No Information	No Information
XYLENE	Proprietary	2.5-10	No Information	No Information
	1330-20-7	1.0-2.5	GHS02-GHS07-GHS08	H226-304-312-315-332-335-373
TITANIUM DIOXIDE	13463-67-7	0.1-1.0	No Information	No Information
ETHYLBENZENE	100-41-4	0.1-1.0	GHS02-GHS07-GHS08	H225-304-315-319-332-373
CRYSTALLINE SILICA	14808-60-7	0.1-1.0	GHS07-GHS08	H332-350-373
METHYL ETHYL KETOXIME	96-29-7	0.1-1.0	GHS05-GHS06-GHS08	H302-310-317-318-351
STODDARD SOLVENT	8052-41-3	0.1-1.0	GHS02-GHS08	H226-304
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	64742-95-6	0.1-1.0	GHS07-GHS08	H304-332
2-ETHYLHEXANOIC ACID COBALT SALT	136-52-7	0.1-1.0	GHS06-GHS08	H302-312-331-361

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



**FIRST AID - INHALATION:** If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**FIRST AID - SKIN CONTACT:** In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

**FIRST AID - EYE CONTACT:** If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

## 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** REMOVE ALL SOURCES OF IGNITION FROM THE SPILL AREA. EVACUATE ALL NON-ESSENTIAL PERSONNEL UPWIND. USING NON-SPARKING TOOLS, SOAK UP SPILLED MATERIAL / SWEEP UP MATERIAL WITH ABSORBENTS AND PLACE IN A CONTAINER FOR DISPOSAL.

## 7. Handling and Storage



**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

**STORAGE:** Keep container closed when not in use. Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT LIMESTONE	5 mg/m3	10 mg/m3	5 mg/m3	N.E.
IRON OXIDE (FE2O3), RESPIRABLE	5 mg/m3 (Respirable fraction)	N.E.	5 mg/m3 (Respirable fraction)	N.E.
POLYURETHANE RESIN	5 mg/m3 (Respirable fraction)	N.E.	10 mg/m3	N.E.
XYLENE	N.E.	N.E.	N.E.	N.E.
TITANIUM DIOXIDE	100 ppm	150 ppm	100 ppm	N.E.
ETHYLBENZENE	10 mg/m3	N.E.	15 mg/m3 (Total dust)	N.E.
CRYSTALLINE SILICA	20 ppm	125 ppm	100 ppm	N.E.
METHYL ETHYL KETOXIME	0.05 mg/m3 (Respirable dust)	N.E.	0.1 mg/m3 (Respirable dust)	N.E.
STODDARD SOLVENT	N.E.	N.E.	N.E.	N.E.
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	100 ppm	N.E.	500 ppm	N.E.
2-ETHYLHEXANOIC ACID COBALT SALT	200 mg/m3	N.E.	400 PPM	500 PPM
	0.02 mg/m3	N.E.	0.1 mg/m3	N.E.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



**SKIN PROTECTION:** Chemical-resistant gloves may be required for individuals with sensitive skin.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



**OTHER PROTECTIVE EQUIPMENT:** Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Thick Red Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Solvent Odor	<b>Odor Threshold:</b>	No Information
<b>Density, lb/gal:</b>	9.34 - 9.74	<b>pH:</b>	No Information
<b>Freeze Point, °C:</b>	No Information	<b>Viscosity:</b>	No Information
<b>Solubility in Water:</b>	No Information	<b>Partition Coefficient, n-octanol/ water:</b>	No Information
<b>Decomposition temperature, °C</b>	No Information		
<b>Boiling Range, °C:</b>	148 - 193	<b>Explosive Limits, %:</b>	N/A
<b>Combustibility:</b>	Supports Combustion	<b>Flash Point, °C:</b>	40
<b>Evaporation Rate:</b>	Slower than Ether	<b>Auto-Ignition Temperature, °C</b>	No Information
<b>Vapor Density:</b>	Heavier than Air	<b>Vapor Pressure, mmHg:</b>	No Information

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Avoid heat, flames, sparks and other sources of ignition. Extremes of temperature and direct sunlight.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames. Strong acids and strong bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Incomplete combustion may produce carbon monoxide and other toxic gases.

## 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness. This product contains crystalline silica, which is considered a hazard by inhalation.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Mist and vapors may cause eye irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Crystalline silica is known to cause silicosis, a noncancerous lung disease. Exposure is by route of inhalation. If material is in a liquid matrix it is unlikely to be inhaled. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

**CARCINOGENICITY:** Crystalline silica has been classified by IARC and NTP as a carcinogen for humans (Group 1) from lab animal studies. Inhalation of crystalline silica can cause cancer. Risk of cancer depends on duration and level of exposure from sanding surfaces or spray mist. When sanding or spraying product use (NIOSH/MSHA approved) respiratory protection. IARC lists Titanium Dioxide, Ethylbenzene and Cobalt/Cobalt compounds as possible human carcinogens (Group 2B)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-47-8	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	> 5,000 mg/kg (Rat)	> 2,000 mg/kg (Rabbit)	N.I.
1317-65-3	LIMESTONE	6,450 mg/kg (Rat)	> 2,000 mg/kg (Rabbit)	N.I.
1309-37-1	IRON OXIDE (FE2O3), RESPIRABLE	> 10,000 mg/kg (Rat)	N.I.	N.I.
Proprietary	POLYURETHANE RESIN	>2000 mg/kg	N.I.	N.I.

1330-20-7	XYLENE	4,300 mg/kg (Rat)	>1,700 mg/kg (Rabbit)	6,350 mg/L, 4 hr (Rat)
13463-67-7	TITANIUM DIOXIDE	> 5,000 mg/kg (Rat)	> 10,000 mg/kg (Rabbit)	N.I.
100-41-4	ETHYLBENZENE	3,500 mg/kg (Rat)	15,433 mg/kg (Rabbit)	17.2 mg/L (Rat)
96-29-7	METHYL ETHYL KETOXIME	930 mg/kg	0.2 mg/kg	N.I.
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	> 5,600 mg/kg	> 4,000 mg/kg	>10.2 mg/l/4hr
136-52-7	2-ETHYLHEXANOIC ACID COBALT SALT	1,300 mg/kg (Rat)	N.I.	N.I.

N.I. = No Information

## 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

## 13. Disposal Information



Product

**DISPOSAL METHOD:** Dispose of material in accordance with applicable federal, state and local regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** REMOVE ALL SOURCES OF IGNITION FROM THE SPILL AREA. EVACUATE ALL NON-ESSENTIAL PERSONNEL UPWIND. USING NON-SPARKING TOOLS, SOAK UP SPILLED MATERIAL / SWEEP UP MATERIAL WITH ABSORBENTS AND PLACE IN A CONTAINER FOR DISPOSAL.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** This product can be transported as a LIMITED QUANTITY for 1 Gallon or less.

<b>DOT Proper Shipping Name:</b>	Paint	<b>Packing Group:</b>	III
<b>DOT Technical Name:</b>	No Information	<b>Hazard SubClass:</b>	No Information
<b>DOT Hazard Class:</b>	3	<b>Resp. Guide Page:</b>	No Information
		<b>DOT UN/NA Number:</b>	UN1263

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Specific target organ toxicity (single or repeated exposure)

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
RESIN	Proprietary
WATER	7732-18-5

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
RESIN	Proprietary
WATER	7732-18-5

**CALIFORNIA PROPOSITION 65 CARCINOGENS****WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYLBENZENE	100-41-4
CRYSTALLINE SILICA	14808-60-7
CUMENE	98-82-8
BENZENE	71-43-2
NAPHTHALENE	91-20-3

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS****WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
BENZENE	71-43-2
TOLUENE	108-88-3

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class** No Information

**16. Other Information**

**Revision Date:** 5/17/2018 **Supersedes Date:** New MSDS  
**Reason for revision:** No Information  
**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**






<b>Health:</b>	*2	<b>Flammability:</b>	2	<b>Reactivity:</b>	0	<b>Personal Protection:</b>	N.I.
----------------	----	----------------------	---	--------------------	---	-----------------------------	------

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225 Highly flammable liquid and vapour.

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	Suspected of causing cancer.
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form.
H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H373	May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02	
GHS05	
GHS06	
GHS07	
GHS08	

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.