

Safety Data Sheet

1. Identification

Product Information: STOV-N

Product Name: Woodsman Semi-Transparent Oil Deck, Siding & Fence (Neutral Base)

Recommended Use: Semi-Transparent Exterior Stain

Application Method: No Information

Supplied by: True Value Manufacturing
201 Jandus Road
Cary, IL 60013
Telephone: (847) 639-5383

Emergency Telephone: (866)257-3981

2. Hazards Identification

EMERGENCY OVERVIEW: No Information

GHS Classification
Carc. 1B, Muta. 1B

Symbol(s) of Product



Signal Word
Danger

GHS HAZARD STATEMENTS

Germ Cell Mutagenicity, category 1B H340 Suspected of causing genetic defects .
Carcinogenicity, category 1B H350 Suspected of causing cancer.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.
P281 Use personal protective equipment as required.
P308+P313 IF exposed or concerned: Get medical advice/attention.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
2-Propanol, 1-(2-butoxy-1-methylethoxy)-	29911-28-2	2.5-10	GHS07	H332
ETHYLENE GLYCOL	107-21-1	1.0-2.5	GHS07	H302-332
PARAFFIN WAX FUME	8002-74-2	1.0-2.5	GHS06	H311
AMORPHOUS SILICA	112945-52-5	0.1-1.0	GHS06	H330
HYDRATED ALUMINUM MAGNESIUM SILICATE	12174-11-7	0.1-1.0	No Information	No Information
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	0.1-1.0	GHS08	H304-340-350
IODOPROPYNYL BUTYLCARBAMATE	55406-53-6	0.1-1.0	GHS05-GHS06-GHS08	H302-317-318-331-372
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	64742-95-6	0.1-1.0	GHS07-GHS08	H304-332-340-350

DIPROPYLENE GLYCOL

25265-71-8

0.1-1.0 GHS06

H300

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

FIRST AID - EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

FIRST AID - INGESTION: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

7. Handling and Storage



HANDLING: KEEP FROM FREEZING

STORAGE: Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
2-Propanol, 1-(2-butoxy-1-methylethoxy)-	N.E.	N.E.	N.E.	N.E.
ETHYLENE GLYCOL	100 mg/m3 Aerosol	N.E.	N.E.	50 PPM, 125 mg/m3
PARAFFIN WAX FUME	N.E.	N.E.	N.E.	N.E.
AMORPHOUS SILICA	N.E.	N.E.	N.E.	N.E.
HYDRATED ALUMINUM MAGNESIUM SILICATE	N.E.	N.E.	N.E.	N.E.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	100 ppm	N.E.	N.E.	N.E.
IODOPROPYNYL BUTYLCARBAMATE	N.E.	N.E.	N.E.	N.E.
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	200 mg/m3	N.E.	400 PPM	500 PPM
DIPROPYLENE GLYCOL	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



SKIN PROTECTION: Sensitive individuals should wear gloves to prevent repeated contact.



EYE PROTECTION: Safety glasses with side-shields



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: Wash hands before eating, drinking, or smoking.

9. Physical and Chemical Properties

Appearance:	Thick Liquid	Physical State:	Liquid
Odor:	Solvent Odor	Odor Threshold:	No Information
Density, g/cm³:	0.000	pH:	No Information
Freeze Point, °C:	No Information	Viscosity:	No Information
Solubility in Water:	No Information	Partition Coefficient, n-octanol/ water:	No Information
Decomposition temperature, °C	No Information		
Boiling Range, °C:	148 - 193	Explosive Limits, %:	N/A
Combustibility:	Does not Support Combustion	Flash Point, °C:	Not Applicable
Evaporation Rate:	Slower Than Ether	Auto-Ignition Temperature, °C	No Information
Vapor Density:	Heavier Than Air	Vapor Pressure, mmHg:	No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND FREEZING.

INCOMPATIBILITY: No Information

HAZARDOUS DECOMPOSITION PRODUCTS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

EFFECT OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.

EFFECT OF OVEREXPOSURE - INGESTION: May be harmful if swallowed. May cause gastrointestinal disturbance.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Under normal use conditions, this product is not expected to cause adverse health effects.

CARCINOGENICITY: No Components listed with NTP, IARC or OSHA

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
29911-28-2	2-Propanol, 1-(2-butoxy-1-methylethoxy)-	3700 mg/kg	>2000 mg/kg	N.I.
107-21-1	ETHYLENE GLYCOL	2000 mg/kg	>3500 mg/kg	N.I.
8002-74-2	PARAFFIN WAX FUME	6450 mg/kg	500 mg (Rabbit, 24hr)	N.I.
112945-52-5	AMORPHOUS SILICA	>5000 mg/kg	>5000 mg/kg	N.I.
64742-47-8	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	>5000 mg/kg	>5000 mg/kg	N.I.
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	>5600 mg/kg	>4000 mg/kg	>10.2 mg/l/4hr
25265-71-8	DIPROPYLENE GLYCOL	14.8 g/kg	>5000 mg/kg (Rabbit, 24hr)	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No Information

13. Disposal Information



Product

DISPOSAL METHOD: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Name: No Information
DOT Technical Name: No Information
DOT Hazard Class: No Information
DOT UN/NA Number: No Information

Packing Group: No Information
Hazard SubClass: No Information
Resp. Guide Page: No Information

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYLENE GLYCOL	107-21-1
AMMONIUM HYDROXIDE	1336-21-6
IODOPROPYNYL BUTYLCARBAMATE	55406-53-6
FORMALDEHYDE	50-00-0

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Water	7732-18-5
WATER	7732-18-5
RESIN	Proprietary
ACRYLIC POLYMER	Proprietary

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Water	7732-18-5
WATER	7732-18-5
RESIN	Proprietary
ACRYLIC POLYMER	Proprietary

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDRATED ALUMINUM MAGNESIUM SILICATE	12174-11-7
CRYSTALLINE SILICA	14808-60-7
FORMALDEHYDE	50-00-0
.alpha.-chlorotoluene; benzyl chloride	100-44-7
ETHYLBENZENE	100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -**CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class No Information

16. Other Information

Revision Date: 7/18/2016 **Supersedes Date:** New MSDS
Reason for revision: No Information
Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	*1	Flammability:	0	Reactivity:	0	Personal Protection:	N.I.
----------------	----	----------------------	---	--------------------	---	-----------------------------	------

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H300 Fatal if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H340 Suspected of causing genetic defects.
H350 Suspected of causing cancer.
H372 Causes damage to organs

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS05



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.